

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Kitson et al.

SERIAL No. Unassigned

EXAMINER: Unassigned

FILED: Herewith

GROUP NO.: Unassigned

TITLE: BISTABLE NEMATIC LIQUID CRYSTAL DEVICE

ATTORNEY DOCKET NO. 30001063

Assistant Commissioner For Patents
Washington, D.C. 20231

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231, on MARCH 23, 2012 (Date of Deposit)

DAVID L. BATES

Name

Signature

PRELIMINARY AMENDMENT

Dear Sir:

Please amend the application as follows:

IN THE CLAIMS

All of the claims, whether amended or not, are shown below for the convenience of the Examiner.

1. (Amended) A bistable nematic liquid crystal device comprising:

a first cell wall and a second cell wall enclosing a layer of nematic liquid crystal material;

electrodes for applying an electric field across at least some of the liquid crystal material;

a surface alignment on the inner surface of at least the first cell wall providing alignment to the liquid crystal molecules;

wherein the surface alignment comprises an array of features which have at least

one of a shape and an orientation to induce the director adjacent the features to adopt two different tilt angles in substantially the same azimuthal direction;

- the arrangement being such that two stable liquid crystal molecular configurations can exist after suitable electrical signals have been applied to the electrodes.

2. A device as claimed in claim 1, wherein the liquid crystal material has negative dielectric anisotropy and wherein the second cell wall has a surface alignment which induces a local homeotropic alignment of the director.

3. (Amended) A device as claimed in claim 1, wherein the features are comprised of posts.

4. (Amended) A device as claimed in claim 1, wherein the features have a height in the range of about 0.5 to 5 μm .

5. (Amended) A device as claimed in claim 1, wherein the features have a height in the range of about 0.9 to 1.3 μm and the spacing between the cell walls is about 3 μm .

6. A device as claimed in claim 3, wherein at least part of the side wall of the posts is tilted with respect to the normal to the plane of the first cell wall.

7. (Amended) A device as claimed in claim 6, wherein the tilt angle is in the range of about 5 to 7°.

8. A device as claimed in claim 6, wherein the tilt angle is about 5°.

9. (Amended) A device as claimed in claim 1, wherein each feature has a width in the range of about 0.2 to 3 μm .

10. (Amended) A device as claimed in claim 1, wherein the features are arranged in one of a random or pseudorandom array.

11. (Amended) A device as claimed in claim 1, wherein the features are spaced in the range of about from 0.1 to 5 μm apart from each other.

12. A device as claimed in claim 1, wherein the liquid crystal material contains a surfactant.

13. (Amended) A device as claimed in claim 1, wherein the features are formed from at least one of a photoresist or a plastics material.

14. A device as claimed in claim 1, further including an analyser and a polariser mounted on the cell walls.

15. (Amended) A device as claimed in claim 1, wherein the features are treated with a material, excluding any material which induces homeotropic alignment in liquid crystal materials.

16. (Amended) A device as claimed in claim 1, wherein the surface alignment on the second cell wall comprises an array of features which have at least one of a shape and an orientation to induce the liquid crystal director adjacent the features to adopt two different tilt angles in substantially the same azimuthal direction.

17. A device as claimed in claim 1, wherein the liquid crystal material has a pleochroic dye dissolved therein.

18. (Amended) A device as claimed in claim 1, wherein at least one of the shape and the orientation of the features is such as to favour only one azimuthal director orientation adjacent the features, and this orientation is the same for each feature.

19. (Amended) A device as claimed in claim 1, wherein at least one of the shape and the orientation of the features is such as to favour only one azimuthal director orientation adjacent the features, and this orientation varies from feature to feature so as to give a scattering effect in one of the two states.

20. A device as claimed in claim 1, wherein the inner surface of the second cell wall is provided with an alignment which induces the local liquid crystal director to adopt a planar alignment in substantially the same azimuthal direction induced by the alignment on the surface of the first cell wall.

21. A device as claimed in claim 1, wherein the liquid crystal director twists between the first cell wall and the second cell wall.

22. A device as claimed in claim 21, wherein the twist is induced by chiral doping of the liquid crystal material.

23. (Amended) A device as claimed in claim 21, wherein the twist is induced by treatment of the second cell wall to produce one of a planar or a tilted planar alignment of the local liquid crystal director at a non-zero angle to the azimuthal direction induced by the features on the first cell wall.

Please add the following new claim:

--24. (Newly added) A device as claimed in claim 1, wherein the features are formed from a material, excluding any material which induces homeotropic alignment in liquid crystal materials.--

Remarks


Claims 1, 3-5, 7, 9-11, 13, 15, 16, 18, 19, and 23 have been amended to eliminate any indefiniteness.

Claim 24 has been added to recite features originally claimed in the alternative in claim 15.

Attached hereto is a marked up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version With Markings to Show Changes Made."

3-23-01
Date

Respectfully submitted,



Paul D. Greeley
Attorney for Applicant(s)
Registration No. 31,019
Ohlandt, Greeley, Ruggiero & Perle, L.L.P.
One Landmark Square, 10th Floor
Stamford, CT 06901-2682
(203) 327-4500

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS

All of the claims, whether amended or not, are shown below for the convenience of the Examiner.

1. (Amended) A bistable nematic liquid crystal device comprising:

a first cell wall and a second cell wall enclosing a layer of nematic liquid crystal material;

electrodes for applying an electric field across at least some of the liquid crystal material;

a surface alignment on the inner surface of at least the first cell wall providing alignment to the liquid crystal molecules;

wherein the surface alignment comprises an array of features which have at least one of a shape and [or] an orientation to induce the director adjacent the features to adopt two different tilt angles in substantially the same azimuthal direction;

the arrangement being such that two stable liquid crystal molecular configurations can exist after suitable electrical signals have been applied to the electrodes.
2. A device as claimed in claim 1, wherein the liquid crystal material has negative dielectric anisotropy and wherein the second cell wall has a surface alignment which induces a local homeotropic alignment of the director.
3. (Amended) A device as claimed in claim 1, wherein the features are comprised of posts.
4. (Amended) A device as claimed in claim 1, wherein the features have a height in the range of about 0.5 to 5 μm .
5. (Amended) A device as claimed in claim 1, wherein the features have a

height in the range of about 0.9 to 1.3 μm and the spacing between the cell walls is about 3 μm .

6. A device as claimed in claim 3, wherein at least part of the side wall of the posts is tilted with respect to the normal to the plane of the first cell wall.

7. (Amended) A device as claimed in claim 6, wherein the tilt angle is in the range of about 5 to 7°.

8. A device as claimed in claim 6, wherein the tilt angle is about 5°.

9. (Amended) A device as claimed in claim 1, wherein each feature has a width in the range of about 0.2 to 3 μm .

10. (Amended) A device as claimed in claim 1, wherein the features are arranged in one of a random or pseudorandom array.

11. (Amended) A device as claimed in claim 1, wherein the features are spaced in the range of about from 0.1 to 5 μm apart from each other.

12. A device as claimed in claim 1, wherein the liquid crystal material contains a surfactant.

13. (Amended) A device as claimed in claim 1, wherein the features are formed from at least one of a photoresist or a plastics material.

14. A device as claimed in claim 1, further including an analyser and a polariser mounted on the cell walls.

15. (Amended) A device as claimed in claim 1, wherein the features are [not] treated with [or formed from] a material, excluding any material which induces homeotropic alignment in liquid crystal materials.

16. (Amended) A device as claimed in claim 1, wherein the surface alignment on the second cell wall comprises an array of features which have at least one of a shape and [/or] an orientation to induce the liquid crystal director adjacent the

features to adopt two different tilt angles in substantially the same azimuthal direction.

17. A device as claimed in claim 1, wherein the liquid crystal material has a pleochroic dye dissolved therein.

18. (Amended) A device as claimed in claim 1, wherein at least one of the shape and [/or] the orientation of the features is such as to favour only one azimuthal director orientation adjacent the features, and this orientation is the same for each feature.

19. (Amended) A device as claimed in claim 1, wherein at least one of the shape and [/or] the orientation of the features is such as to favour only one azimuthal director orientation adjacent the features, and this orientation varies from feature to feature so as to give a scattering effect in one of the two states.

20. A device as claimed in claim 1, wherein the inner surface of the second cell wall is provided with an alignment which induces the local liquid crystal director to adopt a planar alignment in substantially the same azimuthal direction induced by the alignment on the surface of the first cell wall.

21. A device as claimed in claim 1, wherein the liquid crystal director twists between the first cell wall and the second cell wall.

22. A device as claimed in claim 21, wherein the twist is induced by chiral doping of the liquid crystal material.

23. (Amended) A device as claimed in claim 21, wherein the twist is induced by treatment of the second cell wall to produce one of a planar or a tilted planar alignment of the local liquid crystal director at a non-zero angle to the azimuthal direction induced by the features on the first cell wall.

Please add the following new claim:

--24. (Newly added) A device as claimed in claim 1, wherein the features are formed

SERIAL No. Unassigned
GROUP NO.: Unassigned

from a material, excluding any material which induces homeotropic alignment in liquid crystal materials.--